



|                               |                      |
|-------------------------------|----------------------|
| Model                         | JCY-60LS             |
| Surface Size                  | 60x60mm              |
| Position of Micrometer Head   | Left                 |
| Travel Range                  | ±6.5mm               |
| Minimum Reading of Micrometer | 10um                 |
| Guide Type                    | Crossed Roller Guide |
| Load Capacity                 | 5.7Kgf               |
| Parallelism                   | 60um                 |
| Driving Parallelism           | 20um                 |
| Weight                        | 0.42Kg               |
| Material                      | Aluminum             |
| Finish Treatment              | Black Anodizing      |

JCY - 60LS

www.mps-g.com

苏州明普尔电子有限公司



|                               |                      |
|-------------------------------|----------------------|
| Model                         | JCY-60RS             |
| Surface Size                  | 60x80mm              |
| Position of Micrometer Head   | Right                |
| Travel Range                  | ±6.5mm               |
| Minimum Reading of Micrometer | 10µm                 |
| Guide Type                    | Crossed Roller Guide |
| Load Capacity                 | 5.7kgf               |
| Parallelism                   | 60µm                 |
| Driving Parallelism           | 20µm                 |
| Weight                        | 0.42Kg               |
| Material                      | Aluminum             |
| Finish Treatment              | Black Anodizing      |

JCY - 60RS

www.jcy-g.com

东莞市捷成五金机械有限公司